

## United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER OF PATENTS AND TRADEMARKS Washington, D.C. 20231 www.uspto.gov

APPLICATION NO.	FILI	ING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/830,825	25 07/30/2001		Heiner Scheer	10191/1810	2205
26646	7590	03/28/2003			
KENYON & KENYON				EXAMINER	
ONE BROADWAY NEW YORK, NY 10004				TUNG, TA HSUNG	
				ART UNIT	PAPER NUMBER
				1753	
ė.				DATE MAILED: 03/28/2003	

Please find below and/or attached an Office communication concerning this application or proceeding.

	Application No.   Applicant/s)
	Application No. Applicant(s) SCHEER BTAL
Office Action Summary	
	Examiner Group Art Unit (753 Paper No.
-Th MAILING DATE of this communication appears	on th cover sheet beneath th correspondence address—
P riod for Reply	7
A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO OF THIS COMMUNICATION.	EXPIRE MONTH(S) FROM THE MAILING DATE
from the mailing date of this communication.  If the period for reply specified above is less than thirty (30) days, a re  If NO period for reply is specified above, such period shall, by default,  Failure to reply within the set or extended period for reply will, by state	
Status  Responsive to communication(s) filed on	?
☐ This action is <b>FINAL.</b>	
☐ Since this application is in condition for allowance except accordance with the practice under Ex parte Quayle, 1935	or formal matters, <b>prosecution as to the merits is closed</b> in C.D. 1 1; 453 O.G. 213.
Disposition of Claims	
Claim(s) 24-47	is/are pending in the application.
Of the above claim(s)	is/are withdrawn from consideration.
□ Claim(s)	is/are allowed.
□ Claim(s) 2 4 - 47	is/are rejected.
□ Claim(s)	is/are objected to.
□ Claim(s)	
Application Papers	requirement
Application Papers  ☐ The proposed drawing correction, filed on	requirement is □ approved □ disapproved.
Application Papers  ☐ The proposed drawing correction, filed on is/are object	requirement is □ approved □ disapproved.
Application Papers  ☐ The proposed drawing correction, filed on is/are object ☐ The drawing(s) filed on is/are object ☐ The specification is objected to by the Examiner.	requirement is □ approved □ disapproved.
Application Papers  ☐ The proposed drawing correction, filed on is/are object	requirement is □ approved □ disapproved.
Application Papers  The proposed drawing correction, filed on is/are object  The drawing(s) filed on is/are object  The specification is objected to by the Examiner.  The oath or declaration is objected to by the Examiner.  Pri rity under 35 U.S.C. § 119 (a)-(d)	requirement is □ approved □ disapproved. ed to by the Examiner
Application Papers  ☐ The proposed drawing correction, filed on	requirement is □ approved □ disapproved. ed to by the Examiner
Application Papers  ☐ The proposed drawing correction, filed on	requirement  is approved disapproved.  and to by the Examiner  der 35 U.S.C. § 119 (a)–(d).
Application Papers  ☐ The proposed drawing correction, filed on	requirement  is approved disapproved.  ed to by the Examiner  der 35 U.S.C. § 119 (a)–(d).
Application Papers  ☐ The proposed drawing correction, filed on	requirement  is approved disapproved.  ed to by the Examiner  der 35 U.S.C. § 119 (a)–(d).  seived.  seived in Application No.
Application Papers  ☐ The proposed drawing correction, filed on	requirement  is approved disapproved.  det to by the Examiner  der 35 U.S.C. § 119 (a)–(d).  seived.  seived in Application No.
Application Papers  ☐ The proposed drawing correction, filed on	requirement  is approved disapproved.  ed to by the Examiner  der 35 U.S.C. § 119 (a)–(d).  seived. seived in Application No. have been received  Bureau (PCT Rule 17.2(a))
Application Papers  ☐ The proposed drawing correction, filed on	requirement  is approved disapproved.  ed to by the Examiner  der 35 U.S.C. § 119 (a)–(d).  seived. seived in Application No. have been received  Bureau (PCT Rule 17.2(a))
Application Papers  ☐ The proposed drawing correction, filed on	requirement  is approved disapproved.  det oby the Examiner  der 35 U.S.C. § 119 (a)–(d).  seived. seived in Application No. shave been received  Bureau (PCT Rule 17.2(a))
Application Papers  ☐ The proposed drawing correction, filed on	requirement  is approved disapproved.  det oby the Examiner  der 35 U.S.C. § 119 (a)–(d).  seived. seived in Application No. shave been received  Bureau (PCT Rule 17.2(a))  Int rvi w Summary, PTO–413
Application Papers  ☐ The proposed drawing correction, filed on	requirement  is approved disapproved.  det oby the Examiner  der 35 U.S.C. § 119 (a)–(d).  seived. seived in Application No. shave been received  Bureau (PCT Rule 17.2(a))

U.S. Patent and Trademark Office PTO-326 (Rev. 11/00)

Part of Pap r No.

Art Unit: 1102

The restriction requirement is hereby withdrawn.

Claims 24-47 are rejected under 35 U.S.C. 112, first paragraph, as containing subject matter which was not described in the specification in such a way as to enable one skilled in the art to which it pertains, or with which it is most nearly connected, to make and/or use the invention.

The disclosure is inadequate in that the method for forming the sensor element is inadequate. The only description of the method in the specification appears to be at page 4, lines 23-34. From this very brief discussion, it is unclear how the measuring gas chamber and the reference gas channel are formed from the pasty layer of solid electrolyte. Also, is the partition 12 between the measuring gas chamber and the reference gas channel part of the solid electrolyte layer 11b? If yes, why is the partition sectioned as a different material from layer llb? If not, how is the partition formed? Further, how is diffusion barrier 27 formed?

Applicant should note that the test for adequate disclosure is what is actually disclosed, not what may be obvious from the disclosure. This is particular so when applicant is claiming a method for forming the sensor element.

Claim 45, it is not evident what element is this "supporting element". Where is the related discussion in the specification?

Claims 24-47 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

Art Unit: 1102

Claim 24, it is not evident what is the state of the device being claimed. The last line of the claim calls for a ceramic paste. When a ceramic paste layer is in that state, the measuring gas chamber, the reference gas channel and the partition between them are clearly not yet in existence. Correspondingly, the final sensor product would not have a paste layer. So, is applicant claiming the final product, some intermediate precusor, what? For the purpose of this rejection, the claims are construed as to call for the presence of a pasty layer.

Claim 43, lines 4-6, the wording is considered to be misdescriptive. It is not evident how a pasty ceramic layer with a measuring gas chamber and a reference gas channel can be applied to the solid electrolyte foil, because when the ceramic layer is in the form of a paste, no chamber or channel has yet been formed.

Clarification of the claim language by applicant in a response may necessitate a change in the prior art rejection (including the citation of additional prior art). If so, such change would not prevent the finality of any further rejection.

Claim 26, the wording is vague. Does applicant mean that the partition is in contact with the measuring electrode?

Claim 28, the wording is vague. Does applicant mean that the reference electrode contacts the partition?

Claim 31, line 2, --inner-- should be added before "pump" (2d occ) to point out which pump electrode.

Art Unit: 1102

Claim 45, line 2, it is not evident which element is this "supporting element" in the reference gas chamber. Is it the same as the porous ceramic filler material, as recited in claim 40?

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

Claims 24-28, 33-35, 37, 40, 41, 43-47 are rejected under 35 U.S.C. 102(b) as being anticiapted by Friese et al 5,314,604.

Friese discloses a sensor element comprising a zirconia solid electrolyte layer 2 that has a reference gas channel 10. A measuring gas chamber with an inner pump electrode 8-8' can also be considered to be in solid electrolyte 2 because the measuring gas chamber appears to be partly in the electrolyte. Therefore, the measuring gas chamber and the reference gas channel are in the "same layer plane". Element 9 is a measuring electrode, while element 11 is a reference electrode. See col. 3, lines 14-63. At col. 4, lines 15-20, the patent states that the solid electrolytes sheets can be formed by screen printing.

As for claim 27, see figure 1B. As for claim 40, see col. 4, line 31.

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person Art Unit: 1102

having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Claims 24-28, 33-35, 37, 40, 41, 43-47 are rejected under 35 U.S.C. 103(a) as being unpatentable over Friese etal in view of Schneider etal 5,529,677, Jach etal 6,375,816 or Logothetis etal 4,487,680.

If Friese were construed as not to disclose forming a solid electrolyte layer by coating a paste, applicant's claims differ in that respect.

Schneider discloses forming a zirconia layer onto another layer by screen printing a zirconia paste layer thereunto. See col. 4, lines 40-55. Jach discloses forming a ceramic layer 22 that contains a gas chamber 21 onto a solid electrolyte layer by coating a paste of the ceramic material and then sintering. See col. 3, lines 23-57. Logothetis discloses forming a zirconia layer unto another zirconia layer by screen printing. See col. 5, lines 57-67.

Jach's filing date of Dec. 14, 1999 is prior to applicant's filing date but subsequent to applicant's priority date of Aug. 28, 1999. However, Jach is a reference until applicant submits a certified translation of his priority document to substantiate a commonality of subject matter.

It would have been obvious for Friese to form zirconia layer 2 by screen printing onto solid electrolyte layer 1 or 3 in view of Schneider, Jach or Logothetis, since screen printing is a well-known technique for forming films. This is especially true, when Friese itself also discloses (col. 4, line 18) screen printing to be a common technique for joining layers. The incorporation of

Art Unit: 1102

known technique from analogous prior art is within the skill of the art in the absence of unexpected result.

Claim 31 is rejected under 35 U.S.C. 103(a) as being unpatentable over Friese etal, with or without Schneider etal, Jach or Logothetis etal, in view of Ep 678740 or Nakae etal 5,298,147.

This claim further differs by calling for the measuring electrode to be opposite the inner pump electrode.

Ep discloses a measuring electrode 22 opposite an inner pump electrode 16 in a sensor element similar to those of Friese and applicant. See figure 2; col. 11, line 27 to col. 13, line 40. Nakae discloses a measuring electrode 28 opposite an inner pump electrode 27. See figure 2; col. 4, lines 10-59.

It would have been obvious for Friese to locate the measuring electrode and the inner pump electrode opposite each other in view of Ep or Nakae so as to minimize the lateral dimension. Solid electrolyte sensors are typically very small. Any design to minimize a dimension or save space would be desirable.

Claim 32 is rejected under 35 U.S.C. 103(a) as being unpatentable over Friese etal, with or without Schneider etal, Jach or Logothetis etal, in view of Kato etal 6.059,947.

This claim further differs by calling for the inner pump electrode to also serve as the measuring electrode.

Kato discloses electrode 24 serving both as an inner pump electrode and as a measuring electrode. See figure 2; col. 6, line 54 to col. 9, line 19. It would have been obvious for Friese to

Art Unit: 1102

combine the inner pump electrode 8-8' and the measuring electrode 9 into a single electrode so as to save space and material cost.

Claim 36 is rejected under 35 U.S.C. 103(a) as being unpatentable over Friese etal, with or without Schneider etal, Jach or Logothetis etal, in view of Makino etal 5,676,811.

This claim further differs by calling for the reference electrode to be situated on a side of the reference gas channel nearest the large surface of the sensor element exposed to a sample gas mixture.

Makino discloses reference electrode 13 located on a side of a reference gas channel 19 nearest the large surface of a sensor element exposed to a sample mixture. See figure 1; col. 4, line 20 to col. 5, line 23. It would have been obvious for Friese to locate its reference electrode 11 on the opposite surface of the reference gas channel in view of Makino. The incorporation of a known feature functioning as expected from analogous prior art is within the skill of the art.

Claims 38, 39 are rejected under 35 U.S.C. 103(a) as being unpatentable over Friese etal, with or without Schneider etal, Jach or Logothetis etal, in view of Sasayama etal 4,900,425.

These claims further differ by calling for the measuring electrode and the reference electrode to have a portion extending outside of the measuring electrode chamber and the reference gas channel respectively.

Sasayama discloses an electrode 12 having a portion extending outside of a gas space 32. See figures 1-3; col. 2, line 9 to col. 4, line 2. It would have been obvious for Friese to extend a portion of its measuring or reference electrode outside of its gas space in view of Sasayama. The

Art Unit: 1102

incorporation of known features functioning as expected from analogous prior art is within the skill of the art.

Claim 42 is rejected under 35 U.S.C. 103(a) as being unpatentable over Friese etal, with or without Schneider etal, Jach or Logothetis etal, in view of Yamada 4,505,807.

This claim further differs by calling for a heater located about equidistant from the two large surfaces of the sensor element.

Yamada discloses a heater 13 situated about half way up a sensor element. See figures 1-2; col. 4, line 59 to col. 5, line 47. It would have been obvious for Friese to locate its heater about half way up the sensor element in order to provide uniform, efficient heating throughout the sensor element, as suggested at col. 9, line 27 of Yamada.

Claim 45 is rejected under 35 U.S.C. 103(a) as being unpatentable over Friese etal, with or without Schneider etal, Jach or Logothetis etal, in view of Holfelder etal 4,502,939 or Mase etal 4,797,194.

This claim further differs by calling for a support element in the reference gas channel.

Holfelder discloses a porous filler material 42 within a gas channel acting as a support.

See col. 5, lines 12-55. Mase discloses providing supporting means 30, 72 within a gas channel.

See col. 7, line 10; col. 8, line 29.

It would have been obvious for Friese to adopt supporting means within its reference gas channel to prevent the narrowing of the channel and maintain proper diffusion.

Art Unit: 1102

Claims 24-26, 28, 31, 33, 41-44, 46, 47 are rejected under 35 U.S.C. 103(a) as being unpatentable over Ep 678740 in view of Schneider etal, Jach or Logothetis etal.

Ep discloses a sensor element comprising a measuring gas chamber 6 and a referene gas channel 10 located in a same zirconia solid electrolyte layer 4b. An inner pump electrode 16 and a measuring electrode 22 are located in the measuring gas chamber opposite each other, while a reference electrode 24 is located in the reference gas channel. See figure 2; col. 11, line 27 to col. 13, line 9. Applicant's claims differ by calling for the solid electrolyte layer containing the gas chamber and the gas channel to be a ceramic paste.

As discussed before, Schneider, Jach or Logothetis discloses applying a zirconia layer to another zirconia layer by screen printing a zirconia paste thereon. It would have been obvious for Ep to apply zirconia layer 4b onto zirconia layer 4a or 4c by screen printing, since that is a common technique.

Claims 27, 34, 35, 37 are rejected under 35 U.S.C. 103(a) as being unpatentable over Ep in view of Schneider etal, Jach or Logothetis etal and Friese etal.

These claims further differ by calling for the electrodes and the gas chamber to be circular or annular.

Friese discloses a circular or annular configuration for its electrodes and gas chamber. See figure 1B. It would have been obvious for Ep to adopt a circular or annular shape for its electrodes and gas chamber in view of Friese, since the incorporation of known configurations from analogous prior art is within the skill of the art. Also, shape is a matter of design choice.

Art Unit: 1102

This claim further differs by calling for the inner pump electrode to also serve as the measuring electrode. As discussed before, that is rendered obvious by Kato.

Claim 36 is rejected under 35 U.S.C. 103(a) as being unpatentable over Ep in view of Schneider etal, Jach or Logothetis etal and Makino etal.

This claim further differs by calling for the reference electrode to be located on a side of the reference gas channel nearest the large surface of the sensor element exposed to a sample. As discussed before, that is rendered obvious by Makino.

Claims 38, 39 are rejected under 35 U.S.C. 103(a) as being unpatentable over Friese et al in view of Schneider et al, Jach or Logothetis et al and Sasayama et al.

These claims further differ by calling for the measuring electrode and the reference electrode to have a portion extending outside of its respective gas space. As discussed before, that is rendered obvious by Sasayama.

Claims 40, 45 are rejected under 35 U.S.C. 103(a) as being unpatentable over Ep in view of Schneider etal, Jach or Logothetis etal and Holfelder etal or Mase etal.

These claims further differ by calling for the reference gas channel to have a filler support means. As discussed before, that is rendered obvious by Holfelder or Mase.

The subject matter of claims 29 and 30 calling for a tapered reference electrode and the reference electrode/reference gas channel being led around the measuring gas chamber is not seen to be disclosed or fairly suggested by the prior art of record.

Page 11

Application/Control Number: 09/830,825

Art Unit: 1102

In the specification, page 2, line 32 and page 3, line 16 the wording does not read correctly. Applicant should review the entire specification for other informalities.

Roy et al 3,776,831 discloses forming a solid electrolyte layer onto another solid electrolyte layer. See col. 3, line 65 to col. 4, line 18.

The examiner can be reached at 703-308-3329. His supervisor Nam Nguyen can be reached at 703-308-3322. Any general inquiry should be directed to the receptionist at 703-308-0661. A fax number for TC 1700 is 703-872-9310.

Ta Tung

Primary Examiner

Art Unit 1753